



SOLIDEAL MAGNUM • MAGNUM SEMI

TIRE SIZE	RIM SIZE ⁽¹⁾	TREAD PATTERN	HEEL		ACTUAL TIRE DIMENSIONS				WEARABLE HEIGHT		LOAD CAPACITY ⁽²⁾ • Counterbalanced lift trucks			
					Overall diameter		Overall width				Load w/hheel		Steering wheel	
			Normal	Quick	mm	inch	mm	inch	25 km/h • 16 mph		25 km/h • 16 mph			
									kg	lbs	kg	lbs		
3.00 - 4	2.10 - 4	MAG	■		251	9.9	84	3.3	23	0.9	255	550	195	450
3.00 - 4	2.50C - 4	MAG	■		251	9.9	84	3.3	23	0.9	255	550	195	450
4.00 - 4	2.10 - 4	MAG	■		307	12.1	96	3.8	36	1.4	535	1200	410	900
4.00 - 4	2.50C - 4	MAG	■		307	12.1	96	3.8	36	1.4	535	1200	410	900
4.00 - 8	3.00D - 8	MAG	■	■	410	16.1	103	4.1	34	1.3	950	2100	730	1600
5.00 - 8	3.00D - 8	MAG	■	■	450	17.7	122	4.8	39	1.5	1415	3100	1090	2400
15 x 4 1/2 - 8	3.00D - 8	MAG	■	■	376	14.8	114	4.5	28	1.1	1040	2300	800	1750
15 x 4 1/2 - 8	3.25I - 8	MAG	■		376	14.8	114	4.5	26	1.0	1040	2300	800	1750
16 x 6 - 8	4.33R - 8	MAG	■	■	412	16.2	150	5.9	34	1.3	1495	3300	1150	2550
18 x 7 - 8	4.33R - 8	MAG	■	■	454	17.9	157	6.2	46	1.8	2145	4750	1650	3650
5.00 - 9	3.50D - 9	MAG	■		487	19.2	129	5.1	34	1.3	1445	3200	1110	2450
6.00 - 9	4.00E - 9	MAG	■	■	523	20.6	138	5.4	52	2.0	1885	4150	1450	3200
21 x 8 - 9	6.00E - 9	MAG	■	■	517	20.4	187	7.4	48	1.9	2755	6100	2120	4700
140/55 - 9	4.00E - 9	MAG		■	379	14.9	130	5.1	28	1.1	1170	2600	900	2000
6.50 - 10	5.00F - 10	MAG	■	■	566	22.3	162	6.4	55	2.2	2340	5150	1800	3950
7.50 - 10	5.00F - 10	MAG	■	■	631	24.8	180	7.1	68	2.7	3070	6800	2360	5200
7.50 - 10	5.50F - 10	MAG	■	■	631	24.8	180	7.1	68	2.7	3070	6800	2360	5200
23 x 9 - 10	6.50F - 10	MAG	■	■	583	23.0	204	8.0	52	2.0	3445	7600	2650	5850
200/50 - 10	6.50F - 10	MAG	■	■	461	18.1	191	7.5	35	1.4	2470	5450	1900	4200
200/50 - 10	6.50F - 10	MAG SEMI	■	■	461	18.1	191	7.5	35	1.4	2470	5450	1900	4200
25 x 7 - 12	5.00S - 12	MAG	■		635	25.0	172	6.8	58	2.3	2835	6250	2180	4800
7.00 - 12	5.00S - 12	MAG	■	■	652	25.7	172	6.8	61	2.4	2920	6450	2240	4950
7.00 - 12	5.00S - 12	MAG SEMI	■		652	25.7	172	6.8	61	2.4	2920	6450	2240	4950
8.25 - 12	5.00S - 12	MAG	■		723	28.5	187	7.4	65	2.5	3440	7600	2645	5850
23 x 10 - 12	8.00G - 12	MAG	■	■	586	23.1	234	9.2	50	2.0	3770	8300	2900	6400
23 x 12 - 12	10.00G - 12	MAG SEMI	■	■	586	23.1	234	9.2	50	2.0	4485	9900	3450	7600
27 x 10 - 12	8.00G - 12	MAG	■	■	680	26.8	248	9.7	64	2.5	3900	8600	3000	6600
150/100 - 13 (23 x 5)	3.75P - 13	MAG	■	■	621	24.4	146	5.7	46	1.8	1715	3800	1320	2900
6.00 - 15	4.50E - 15SDC	MAG	■		698	27.5	160	6.3	44	1.7	2725	6000	2095	4600
7.00 - 15	5.50 - 15	MAG	■	■	729	28.7	179	7.0	60	2.3	3545	7850	2725	6000
7.00 - 15	6.00 - 15	MAG	■		729	28.7	179	7.0	60	2.3	3545	7850	2725	6000
7.50 - 15	5.50 - 15	MAG	■	■	752	29.6	199	7.8	62	2.4	3900	8600	3000	6600
7.50 - 15	6.00 - 15	MAG	■	■	752	29.6	199	7.8	62	2.4	3900	8600	3000	6600
7.50 - 15	6.50 - 15	MAG	■	■	752	29.6	199	7.8	62	2.4	3900	8600	3000	6600
8.25 - 15	5.50 - 15	MAG	■	■	813	32.0	212	8.3	72	2.8	4600	10150	3540	7800
8.25 - 15	6.00 - 15	MAG	■	■	813	32.0	212	8.3	72	2.8	4750	10500	3650	8050
8.25 - 15	6.50 - 15	MAG	■	■	813	32.0	212	8.3	72	2.8	4750	10500	3650	8050
28 x 9 - 15	7.00 - 15	MAG	■	■	687	27.0	218	8.6	54	2.1	3770	8300	2900	6400
355/50 - 15	9.75 - 15	MAG	■	■	712	28.0	295	11.6	52	2.0	5525	12200	4250	9400
355/50 - 15	9.75 - 15	MAG SEMI		■	712	28.0	295	11.6	52	2.0	5525	12200	4250	9400
250 - 15	7.00 - 15	MAG	■	■	716	28.2	225	8.9	60	2.4	4750	10500	3650	8050
250 - 15	7.50 - 15	MAG	■	■	716	28.2	225	8.9	60	2.4	4750	10500	3650	8050
300 - 15	8.00 - 15	MAG	■	■	815	32.1	257	10.1	75	3.0	5850	12900	4500	9950
310 - 15 EW	8.00V - 15	MAG	■		819	32.2	312	12.3	75	3.0	6175	13650	4750	10500



TIRE SIZE	RIM SIZE ⁽¹⁾	TREAD PATTERN	HEEL		ACTUAL TIRE DIMENSIONS				WEARABLE HEIGHT		LOAD CAPACITY ⁽²⁾ • Counterbalanced lift trucks			
					Overall diameter		Overall width				Load w/heel		Steering wheel	
			Normal	Quick	mm	inch	mm	inch	25 km/h • 16 mph		25 km/h • 16 mph			
									kg	lbs	kg	lbs		
355/65 - 15	9.75 - 15	MAG	■	■	819	32.2	312	12.3	75	2.9	7800	17200	6000	13250
7.50 - 16	6.00 - 16	MAG	■		794	31.3	210	8.3	70	2.7	3965	8750	3050	6750
10.00 - 20	6.50 - 20	MAG	■		1035	40.7	255	10.0	82	3.2	5850	12900	4875	10750
10.00 - 20	7.00 - 20	MAG	■		1035	40.7	255	10.0	82	3.2	6000	13250	5000	11050
10.00 - 20	7.50 - 20	MAG	■	■	1035	40.7	255	10.0	82	3.2	6000	13250	5000	11050
10.00 - 20	8.00 - 20	MAG	■	■	1035	40.7	255	10.0	82	3.2	6000	13250	5000	11050
11.00 - 20	7.50 - 20	MAG	■	■	1060	41.7	256	10.1	96	3.8	6540	14450	5450	12050
11.00 - 20	8.00 - 20	MAG	■	■	1060	41.7	256	10.1	96	3.8	6540	14450	5450	12050
12.00 - 20	8.00 - 20	MAG	■		1090	42.9	283	11.1	88	3.4	7560	16700	6300	13900
12.00 - 20	8.50 - 20	MAG	■		1090	42.9	283	11.1	88	3.4	7560	16700	6300	13900
12.00 - 20	10.00 - 20	MAG SEMI	■		1090	42.9	334	13.1	88	3.4	8520	18800	7100	15650
14.00 - 24	10.00 - 24IRA	MAG	■		1320	52.0	333	13.1	109	4.3	11100	24500	9250	20400
14.00 - 25	11.25 - 25	MAG	■		1334	52.5	383	15.1	105	4.1	12480	27550	10400	22950
16.00 - 25	11.25 - 25	MAG	■		1445	56.9	416	16.4	125	4.9	15000	33100	12500	27600

Remarks

(1) Check rim for size, especially on width, as this should correspond to tire base marking. Check also max. load of rim with rim manufacturer, as wheel load will be restricted by lowest load capacity, either the one given by the rim or by the tire.

(2) The speeds quoted in the table are the maximum speeds of the unloaded vehicle. An increase in load capacity for lower speeds is not permitted. For details please contact the technical department. Loads are valid for intermittent service only, they do not include the additional weight of the tires.



SOLIDEAL HT • RIB • MIL • LUG • SM

TIRE SIZE	RIM SIZE ⁽¹⁾	TREAD PATTERN	HEEL		ACTUAL TIRE DIMENSIONS				WEARABLE HEIGHT		LOAD CAPACITY ⁽²⁾ • Counterbalanced lift trucks			
					Overall diameter		Overall width				Load w/hheel		Steering wheel	
			Normal	Quick	mm	inch	mm	inch	25 km/h • 16 mph		25 km/h • 16 mph			
									kg	lbs	kg	lbs		
4.00 - 4	2.10 - 4	MIL	■		305	12.0	98	3.9	32	1.3	535	1200	410	900
4.00 - 4	2.50C - 4	MIL	■		305	12.0	98	3.9	32	1.3	535	1200	410	900
3.00 - 5	2.15B - 5	LUG	■		267	10.5	78	3.1	24	0.9	435	950	335	750
3.50 - 5	3.00SP - 5	LUG	■		298	11.7	101	4.0	32	1.2	520	1150	400	900
10.5 x 4 - 6	3.25A - 6	RIB	■		267	10.5	100	3.9	17	0.6	620	1350	475	1050
140/55 - 6	4.50E - 6	RIB	■		310	12.2	140	5.5	25	1.0	1075	2350	825	1800
100/50 - 8	2.50C - 8	SM	■		302	11.9	102	4.0	22	0.9	710	1550	545	1200
100/50 - 8	3.00D - 8 - 8	SM	■		302	11.9	102	4.0	22	0.9	710	1550	545	1200
100/80 - 8	2.50C - 8	SM	■		359	14.1	104	4.1	22	0.9	755	1650	580	1300
4.00 - 8	2.50C - 8	HT	■		406	16.0	101	4.0	35	1.4	950	2100	730	1600
4.00 - 8	2.50C - 8	RIB	■		406	16.0	101	4.0	25	1.0	950	2100	730	1600
4.00 - 8	3.00D - 8	HT	■	■	406	16.0	103	4.1	35	1.4	950	2100	730	1600
4.00 - 8	3.00D - 8	RIB	■		406	16.0	101	4.0	25	1.0	950	2100	730	1600
4.00 - 8	3.75 - 8	RIB	■		407	16.0	121	4.8	37	1.4	1010	2250	775	1700
5.00 - 8	3.00D - 8	HT	■	■	454	17.9	112	4.4	39	1.5	1415	3100	1090	2400
5.00 - 8	3.00D - 8	SM	■	■	453	17.8	114	4.5	39	1.5	1415	3100	1090	2400
5.00 - 8	3.25I - 8	HT	■		454	17.9	112	4.4	39	1.5	1415	3100	1090	2400
5.00 - 8	3.75 - 8	RIB	■		451	17.8	135	5.3	41	1.6	1500	3300	1155	2550
15 x 4 1/2 - 8	3.00D - 8	HT	■	■	377	14.8	113	4.4	31	1.2	1040	2300	800	1750
15 x 4 1/2 - 8	3.00D - 8	SM	■	■	377	14.8	116	4.6	29	1.1	1040	2300	800	1750
15 x 4 1/2 - 8	3.00D - 8	RIB	■	■	377	14.8	116	4.6	29	1.1	1040	2300	800	1750
15 x 4 1/2 - 8	3.25I - 8	HT	■		377	14.8	116	4.6	31	1.2	1040	2300	800	1750
15 x 4 1/2 - 8	3.25I - 8	RIB	■		377	14.8	116	4.6	29	1.1	1040	2300	800	1750
15 x 4 1/2 - 8	3.25I - 8	SM	■		377	14.8	116	4.6	29	1.1	1040	2300	800	1750
16 x 6 - 8	4.33R - 8	HT	■	■	409	16.1	153	6.0	29	1.1	1495	3300	1150	2550
16 x 6 - 8	4.33R - 8	SM	■	■	409	16.1	153	6.0	29	1.1	1495	3300	1150	2550
18 x 7 - 8	4.33R - 8	HT	■	■	448	17.6	155	6.1	41	1.6	2145	4750	1650	3650
18 x 7 - 8	4.33R - 8	SM	■	■	450	17.7	155	6.1	42	1.7	2145	4750	1650	3650
18 x 9 - 8	7.00E - 8	HT	■		457	18.0	214	8.4	40	1.6	2535	5600	1950	4300
6.00 - 9	4.00E - 9	HT	■	■	517	20.4	134	5.3	48	1.9	1885	4150	1450	3200
6.00 - 9	4.00E - 9	SM	■	■	517	20.4	134	5.3	48	1.9	1885	4150	1450	3200
6.00 - 9	4.00E - 9	RIB	■		517	20.4	134	5.3	48	1.9	1885	4150	1450	3200
16 x 5 - 9	3.50D - 9	RIB	■		410	16.1	126	5.0	24	0.9	1050	2300	810	1800
16 x 5 - 9	4.00E - 9	RIB	■		406	16.0	129	5.1	24	0.9	1050	2300	810	1800
18 x 6 - 9	4.00E - 9	SM	■	■	452	17.8	145	5.7	41	1.6	1625	3600	1250	2750
140/55-9	4.00E - 9	RIB		■	379	14.9	130	5.1	28	1.1	1170	2600	900	2600
21 x 8 - 9	6.00E - 9	HT	■	■	518	20.4	183	7.2	46	1.8	2755	6100	2120	4700
6.50 - 10	5.00F - 10	HT	■	■	566	22.3	158	6.2	52	2.0	2340	5150	1800	3950
6.50 - 10	5.00F - 10	SM	■	■	566	22.3	158	6.2	52	2.0	2340	5150	1800	3950
6.50 - 10	5.50F - 10	HT	■		566	22.3	158	6.2	52	2.0	2340	5150	1800	3950
6.50 - 10	5.50F - 10	SM	■		566	22.3	158	6.2	52	2.0	2340	5150	1800	3950
7.50 - 10	5.00F - 10	HT	■		629	24.8	181	7.1	66	2.6	3070	6800	2360	5200
7.50 - 10	5.50F - 10	HT	■		629	24.8	181	7.1	66	2.6	3070	6800	2360	5200
21 x 7 - 10	5.00F - 10	SM	■	■	524	20.6	162	6.4	55	2.2	2210	4900	1700	3750



SOLIDEAL HT • RIB • MIL • LUG • SM

TIRE SIZE	RIM SIZE ⁽¹⁾	TREAD PATTERN	HEEL		ACTUAL TIRE DIMENSIONS				WEARABLE HEIGHT		LOAD CAPACITY ⁽²⁾ • Counterbalanced lift trucks			
					Overall diameter		Overall width				Load w/h		Steering wheel	
			Normal	Quick	mm	inch	mm	inch	25 km/h • 16 mph		25 km/h • 16 mph			
									kg	lbs	kg	lbs		
23 x 9 - 10	6.50F - 10	HT	■	■	574	22.6	200	7.9	52	2.0	3445	7600	2650	5850
180/60 - 10	5.00F - 10	RIB		■	454	17.9	160	6.3	33	1.3	2405	5300	1850	4100
200/50 - 10	6.50F - 10	HT	■	■	457	18.0	190	7.5	32	1.3	2470	5450	1900	4200
200/50 - 10	6.50F - 10	RIB	■	■	457	18.0	198	7.8	32	1.2	2470	5450	1900	4200
7.00 - 12	5.00S - 12	HT	■	■	650	25.6	160	6.3	55	2.2	2920	6450	2240	4950
7.00 - 12	5.00S - 12	SM	■	■	654	25.7	161	6.3	57	2.2	2920	6450	2240	4950
8.25 - 12	5.00S - 12	SM	■		721	28.4	187	7.4	65	2.6	3440	7600	2645	5850
23 x 10 - 12	8.00G - 12	HT	■	■	586	23.1	233	9.2	45	1.8	3770	8300	2900	6400
23 x 10 - 12	8.00G - 12	SM		■	586	23.1	233	9.2	46	1.8	3770	8300	2900	6400
27 x 10 - 12	8.00G - 12	HT	■	■	675	26.6	242	9.5	61	2.4	3900	8600	3000	6600
27 x 10 - 12	8.00G - 12	SM	■	■	683	26.9	242	9.5	65	2.6	3900	8600	3000	6600
5.50 - 15	4.50E - 15SDC	HT	■		665	26.2	154	6.1	50	2.0	2430	5350	1870	4150
7.00 - 15	5.50 - 15	HT	■		724	28.5	180	7.1	50	2.0	3545	7850	2725	6000
7.00 - 15	6.00 - 15	HT	■		724	28.5	180	7.1	50	2.0	3545	7850	2725	6000
7.50 - 15	5.50 - 15	HT	■	■	743	29.3	194	7.6	56	2.2	3900	8600	3000	6600
7.50 - 15	6.00 - 15	HT	■		743	29.3	194	7.6	56	2.2	3900	8600	3000	6600
7.50 - 15	6.50 - 15	HT	■		743	29.3	194	7.6	56	2.2	3900	8600	3000	6600
8.25 - 15	5.50 - 15	HT	■		805	31.7	203	8.0	65	2.6	4600	10150	3540	7800
8.25 - 15	6.00 - 15	HT	■		805	31.7	203	8.0	70	2.8	4750	10500	3650	8050
8.25 - 15	6.50 - 15	HT	■	■	805	31.7	203	8.0	70	2.8	4750	10500	3650	8050
8.25 - 15	6.50 - 15	SM	■	■	810	31.9	203	8.0	73	2.9	4750	10500	3650	8050
28 x 9 - 15	6.50 - 15	HT	■		690	27.2	202	8.0	52	2.0	3770	8300	2900	6400
28 x 9 - 15	7.00 - 15	HT	■	■	690	27.2	218	8.6	52	2.0	3770	8300	2900	6400
28 x 12.5 - 15 (355/45 - 15)	9.75 - 15	HT	■	■	701	27.6	302	11.9	46	1.8	5525	12200	4250	9400
250 - 15	7.00 - 15	HT	■	■	713	28.1	209	8.2	59	2.3	4750	10500	3650	8050
250 - 15	7.50 - 15	HT	■		709	27.9	214	8.4	57	2.2	4750	10500	3650	8050
300 - 15	8.00 - 15	HT	■	■	809	31.9	258	10.2	68	2.7	5850	12900	4500	9950
300 - 15	8.00 - 15	SM	■	■	809	31.9	258	10.2	69	2.7	5850	12900	4500	9950
355/65 - 15	9.75 - 15	HT	■	■	809	31.9	302	11.9	68	2.7	7800	17200	6000	13250
6.50 - 16	5.50 - 16	HT	■		743	29.3	194	7.6	60	2.4	2600	5750	2000	4400
6.50 - 16	6.00 - 16	HT	■		743	29.3	194	7.6	60	2.4	2600	5750	2000	4400
7.50 - 16	5.50 - 16	HT	■	■	794	31.3	210	8.3	76	3.0	3965	8750	3050	6750
7.50 - 16	6.00 - 16	HT	■		794	31.3	210	8.3	76	3.0	3965	8750	3050	6750
7.50 - 20	6.50 - 20	HT	■		891	35.1	210	8.3	53	2.1	3900	8600	3250	7150
8.25 - 20	6.50 - 20	HT	■		968	38.1	207	8.1	73	2.9	4380	9650	3650	8050
8.25 - 20	6.50 - 20	SM	■		968	38.1	210	8.3	74	2.9	4380	9650	3650	8050
8.25 - 20	7.00 - 20	HT	■		968	38.1	220	8.7	73	2.9	4380	9650	3650	8050
8.25 - 20	7.00 - 20	SM	■		968	38.1	220	8.7	74	2.9	4380	9650	3650	8050
8.25 - 20	7.50 - 20	HT	■		968	38.1	220	8.7	73	2.9	4650	10250	3875	8050
8.25 - 20	7.50 - 20	SM	■		968	38.1	220	8.7	74	2.9	4650	10250	3875	8050
9.00 - 20	6.50 - 20	HT	■		974	38.3	224	8.8	73	2.9	5400	11900	4500	9950
9.00 - 20	7.00 - 20	HT	■		974	38.3	224	8.8	73	2.9	5400	11900	4500	9950
9.00 - 20	7.50 - 20	HT	■		974	38.3	224	8.8	73	2.9	5400	11900	4500	9950
10.00 - 20	7.00 - 20	HT	■		1007	39.6	248	9.8	78	3.1	6000	13250	5000	11050



SOLIDEAL HT • RIB • MIL • LUG • SM

TIRE SIZE	RIM SIZE ⁽¹⁾	TREAD PATTERN	HEEL		ACTUAL TIRE DIMENSIONS				WEARABLE HEIGHT		LOAD CAPACITY ⁽²⁾ • Counterbalanced lift trucks			
					Overall diameter		Overall width				Load wheel		Steering wheel	
			Normal	Quick	mm	inch	mm	inch	mm	inch	25 km/h • 16 mph		25 km/h • 16 mph	
											kg	lbs	kg	lbs
10.00 - 20	7.00 - 20	SM	■		1015	40.0	248	9.8	81	3.2	6000	13250	5000	11050
10.00 - 20	7.50 - 20	HT	■	■	1007	39.6	248	9.8	78	3.1	6000	13250	5000	11050
10.00 - 20	7.50 - 20	SM	■	■	1015	40.0	248	9.8	81	3.2	6000	13250	5000	11050
10.00 - 20	8.00 - 20	HT	■		1007	39.6	248	9.8	78	3.1	6000	13250	5000	11050
10.00 - 20	8.00 - 20	SM	■		1015	40.0	248	9.8	81	3.2	6000	13250	5000	11050
12.00 - 20	8.00 - 20	HT	■		1088	42.8	259	10.2	84	3.3	7560	16700	6300	13900
12.00 - 20	8.00 - 20	SM	■		1088	42.8	265	10.4	84	3.3	7560	16700	6300	13900
12.00 - 20	8.50 - 20	HT	■		1094	43.1	259	10.2	84	3.3	7560	16700	6300	13900
12.00 - 20	8.50 - 20	SM	■		1088	42.8	265	10.2	84	3.3	7560	16700	6300	13900
12.00 - 20	10.00 - 20	SM	■		1088	42.8	316	12.4	84	3.3	8520	18800	7100	15650
12.00 - 24	8.00TG - 24	HT	■		1178	46.4	278	10.9	99	3.9	8040	17750	6700	14800
12.00 - 24	8.50 - 24IRA	HT	■		1178	46.4	278	10.9	99	3.9	8040	17750	6700	14800
12.00 - 24	10.00 - 24IRA	SM	■		1216	47.9	326	12.8	96	3.8	9000	19850	7500	16550
355/85 - 24 (48.5 x 14 - 24)	11.25 - 24IRA	SM	■		1216	47.9	377	14.8	96	3.8	10800	23850	9000	19850
355/85 - 24 (48.5 x 14 - 24)	12.00 - 24IRA	SM	■		1216	47.9	377	14.8	96	3.8	10800	23850	9000	19850
14.00 - 24	10.00 - 24IRA	HT	■		1320	52.0	333	13.1	112	4.4	11100	24500	9250	20400

HT: Planned phase out by December 2012.

ALSO AVAILABLE IN:

GREY NM ➔ *Special non-marking compound with best overall performance and life*



SOLIDEAL XTREME

TIRE SIZE	RIM SIZE ⁽¹⁾	TREAD PATTERN	HEEL		ACTUAL TIRE DIMENSIONS				WEARABLE HEIGHT		LOAD CAPACITY ⁽²⁾ • Counterbalanced lift trucks			
					Overall diameter		Overall width				Load wheel		Steering wheel	
			Normal	Quick	mm	inch	mm	inch	25 km/h • 16 mph		25 km/h • 16 mph			
									kg	lbs	kg	lbs		
5.00 - 8	3.00D - 8	XTR	■	■	450	17.7	122	4.8	39	1.5	1415	3100	1090	2400
15 x 4 1/2 - 8	3.00D - 8	XTR	■	■	376	14.8	114	4.5	28	1.1	1040	2300	800	1750
16 x 6 - 8	4.33R - 8	XTR	■	■	412	16.2	150	5.9	34	1.3	1495	3300	1150	2550
18 x 7 - 8	4.33R - 8	XTR	■	■	451	17.8	153	6.0	46	1.8	2145	4750	1650	3650
6.00 - 9	4.00E - 9	XTR	■	■	524	20.6	138	5.4	52	2.0	1885	4150	1450	3200
21 x 8 - 9	6.00E - 9	XTR	■	■	519	20.4	187	7.4	49	1.9	2755	6100	2120	4700
140/55 - 9	4.00E - 9	XTR		■	377	14.8	130	5.1	28	1.1	1170	2600	900	2000
6.50 - 10	5.00F - 10	XTR	■	■	566	22.3	162	6.4	55	2.2	2340	5150	1800	3950
180/60 - 10	5.00F - 10	XTR		■	452	17.8	160	6.3	33	1.3	2405	5300	1850	4100
23 x 9 - 10	6.50F - 10	XTR	■	■	583	23.0	204	8.0	52	2.0	3445	7600	2650	5850
200/50 - 10	6.50F - 10	XTR	■	■	461	18.1	191	7.5	35	1.4	2470	5450	1900	4200
7.00 - 12	5.00S - 12	XTR	■	■	650	25.6	168	6.6	63	2.5	2920	6450	2240	4950
23 x 10 - 12	8.00G - 12	XTR	■	■	586	23.1	234	9.2	45	1.8	3770	8300	2900	6400
27 x 10 - 12	8.00G - 12	XTR	■	■	680	26.6	244	9.6	64	2.5	3900	8600	3000	6600
7.00 - 15	5.50 - 15	XTR	■	■	729	28.7	179	7.0	60	2.3	3545	7850	2725	6000
7.00 - 15	6.00 - 15	XTR	■		729	28.7	179	7.0	60	2.3	3545	7850	2725	6000
7.50 - 15	5.50 - 15	XTR	■	■	752	29.6	199	7.8	62	2.4	3900	8600	3000	6600
7.50 - 15	6.00 - 15	XTR	■	■	752	29.6	199	7.8	62	2.4	3900	8600	3000	6600
7.50 - 15	6.50 - 15	XTR	■	■	752	29.6	199	7.8	62	2.4	3900	8600	3000	6600
8.25 - 15	6.50 - 15	XTR	■	■	813	32.0	212	8.3	72	2.8	4750	10500	3650	8050
28 x 9 - 15	7.00 - 15	XTR	■	■	687	27.0	218	8.6	54	2.1	3770	8300	2900	6400
28 x 12.5 - 15 (355/45 - 15)	9.75 - 15	XTR	■	■	689	27.1	291	11.5	46	1.8	5525	12200	4250	9400
250 - 15	7.00 - 15	XTR	■	■	719	28.3	225	8.9	62	2.4	4750	10500	3650	8050
250 - 15	7.50 - 15	XTR	■	■	719	28.3	225	8.9	62	2.4	4750	10500	3650	8050
300 - 15	8.00 - 15	XTR	■	■	815	32.1	257	10.1	75	3.0	5850	12900	4500	9950
355/65 - 15	9.75 - 15	XTR	■	■	819	32.2	312	12.3	75	2.9	7800	17200	6000	13250
10.00 - 20	7.00 - 20	XTR	■		1035	40.7	255	10.0	82	3.2	6000	13250	5000	11050
10.00 - 20	7.50 - 20	XTR	■	■	1035	40.7	255	10.0	82	3.2	6000	13250	5000	11050
10.00 - 20	8.00 - 20	XTR	■	■	1035	40.7	255	10.0	82	3.2	6000	13250	5000	11050
12.00 - 20	8.00 - 20	XTR	■		1090	42.9	283	11.1	88	3.4	7560	16700	6300	13900
12.00 - 20	8.50 - 20	XTR	■		1090	42.9	283	11.1	88	3.4	7560	16700	6300	13900
12.00 - 20	10.00 - 20	XTR	■		1090	42.9	283	11.1	88	3.4	8520	18800	7100	15650